




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : D06F 37/00, 37/26	A1	(11) International Publication Number: WO 95/17543 (43) International Publication Date: 29 June 1995 (29.06.95)
(21) International Application Number: PCT/EP94/03941 (22) International Filing Date: 28 November 1994 (28.11.94) (30) Priority Data: PN93U000036 23 December 1993 (23.12.93) IT (71) Applicant (for all designated States except US): ZANUSSI ELETTRODOMESTICI S.p.A. [IT/IT]; Via Giardini Cattaneo, 3, I-33170 Pordenone (IT). (72) Inventor; and (75) Inventor/Applicant (for US only): DURAZZANI, Piero [IT/IT]; Via Lazio, 7, I-33080 Porcia (IT). (74) Agents: GIUGNI, Valter et al.; Propria Protezione Proprietà Industriale s.r.l., Via Mazzini, 13, I-33170 Pordenone (IT).		(81) Designated States: CN, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: IMPROVEMENT IN THE WASHING TUB OF A CLOTHES WASHING MACHINE



(57) Abstract

Clothes washing machine provided with a washing tub made of plastic material and comprising a rear wall (2), a passing-through hub (3) provided at the centre of said rear wall and inserted in its central hub-holding portion (4) for supporting the bearing (7) used to support the central shaft (5) of the drum (6), wherein said hub includes a first perimetral sleeve (8) adapted to be inserted from inside the tub, the outer cylindrical edge thereof being adapted to engage against the inner edge of said cylindrical central hub-holding portion (4), a second sleeve (9) capable of being inserted from outside the tub into the inner cylindrical cavity of said first sleeve, the outer edge thereof being adapted to engage, preferably in a screw-like manner, against the inner edge of said first perimetral sleeve (8). Said first perimetral sleeve is provided with a flange (10) having its projecting rim abutting against the inner wall of the tub, while said second sleeve (9) is provided with a flange (11) having its projecting rim abutting against the outer wall of the tub.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

IMPROVEMENT IN THE WASHING TUB OF A CLOTHES WASHING MACHINE

DESCRIPTION

The present invention refers to a clothes washing machine, particularly of the household type, provided with an improved type of washing tub made of plastic material.

5 Although the present invention refers specially to a washing machine of the front-loading type, and for greater convenience of exemplification the following description is actually referred to such a type of washing machine, it can in an advantageous manner be applied also to other types of
10 washing machines, in particular to the ones that are loaded from the top and have their drum rotating about an horizontal axis.

15 Plastic washing tubs for clothes washing machines are known to substantially comprise a rigid structure forming the peripheral cylindrical envelope and the rear circular wall, and a front wall having a circular shape, too, which is sometimes separated and is capable of being attached to said rigid structure by means of per se known fastening means.

20 In correspondence of the rear wall, preferably radial ribs

are provided in a usually integral way so as to increase the strength of the tub, said ribs being arranged radially from the central portion of said rear wall, as this is for instance illustrated in the Italian patent application no. PN91U000040.

5 A through-hole, in which the shaft supporting and rotatably driving the drum housed within the tub is inserted, is provided in correspondence of said central portion of the rear wall, said shaft being shrink-fitted, outside the tub, into a
10 pulley on which a belt is acting to transmit the motion needed to rotatably drive the drum.

To support said shaft and enable it to rotate under the lowest possible friction effect, as well as to ensure an
15 adequate sealing effect against washing liquor leaking therethrough, such a hole is usually provided with a coaxially arranged hub carrying the bearings for the shaft and normally locked against the inside wall of the hole with known locking means, such as for instance by means of screws or
20 through a press-fitting arrangement or again by moulding the plastics of the tub directly over said hub. The latter is further joined to an external flange adhering to the wall of the tub, and in particular to the portions in relief thereof, said flange being fastened to said wall using known fastening
25 means, preferably a plurality of through-bolts or screws.

The provision of such a hub, if on the one hand it is required to ensure both the support of the shaft and a water-tight sealing of the tub, has the drawback that the hub itself
30 is directly exposed to the relatively high temperatures to which the washing liquor is usually heated up, said washing liquor touching directly the central portion of the rear wall of the tub.

35 This fact, owing to the mechanical action exerted by the rotating shaft against said hub, leads to a gradual stressing of the plastic material which, after a certain period,

undergoes an aging process with a decay in its overall mechanical properties that may become visible through such failures as a loss of tightness (water leakage) or the hub becoming loose from its plastic seat.

Such a development is not effectively opposed by the external fastening of the afore cited flange, owing to the slack that gradually builds up in the holes accomodating said through-bolts or screws.

Furthermore, in the case of a replacement of the bearing or any other repair work to be done under removal of the drum, it is absolutely necessary that said screws or bolts be first loosened and this, if performed repeatedly, leads eventually to a permanent deformation of the plastic material around said fastening elements, so that the need arises to ultimately replace the tub itself. Furthermore, it should be emphasized that the assembly of a great number of fastening screws and/or bolts to the tub turns out to be rather expensive due to both the required processing work and the amount of material used.

It therefore is a purpose of the present invention to provide a washing tub having superior structural and functional characteristics with respect to prior-art tubs, which is capable of ensuring long-term resistance to risks of decay and resulting loosening of the hub, through the application of a particular jaw-type clamping apparatus as described in the appended claims.

The invention will be more readily understood from the description which is given below by way of non-limiting example with reference to the accompanying drawings, in which:

- Figure 1 is a cross-section view of the bearing area of a washing tub according to the present invention;

- Figure 2 is a view from the inside of the same area

appearing in Figure 1;

- Figure 3 is a view from the outside of the same area appearing in Figure 1;

- Figures 4, 4a and 4b are a cross-section view and two opposite views from the outside, respectively, of a feature according to the present invention;

- Figures 5, 5a and 5b are a cross-section view and two opposite views from the outside, respectively, of a second feature according to the present invention;

- Figure 6 is a view of a variant of the feature shown in Figure 4.

Referring now to Figures 1 and 2, let us look at a washing tub made of plastic material and comprising a rear wall 2 closing a cylindrically shaped peripheral envelope (not shown). In the central portion 4 of said rear wall 2 there is provided a through-hole in which a hub 3 is housed to support the shaft 5 used to sustain and rotatably drive the drum 6.

Said hub 3 consists of two distinct parts that must be assembled in a pre-established order: first of all, a first perimetral cylindrical sleeve 8 is press-fitted in some appropriate, known manner to get inserted in a firm and water-tight way into said through-hole provided in said central portion 4; then a second cylindrical sleeve 9 adapted to get inserted into said first sleeve is fitted accordingly, said two sleeves being capable of mutually engage their respective cylindrical matching surfaces, preferably by providing them with a threading so that they can be screwed tightly on.

The second cylindrical sleeve 9 is arranged in a per se known manner so as to be able to house the bearings 7

supporting the shaft 5.

5 With such an arrangement, disassembling the shaft, and the drum with it, turns actually out to be a most easily and quickly performed operation. In fact, loosening the perimetral sleeve from the peripheral sleeve is all that is needed to obtain the separation of the tub from the drum, while such an operation is easily reversed to also re-assemble said component parts, without this causing any particular stress to be exerted on the involved portion of the plastic wall of the tub.

10 The present invention enables various improvements to be achieved. First of all, both the first perimetral sleeve (Figure 4) and the second sleeve arranged inside the first one (Figure 5) are provided with respective outer flanges 10, 11, of which the flange 10 associated with the peripheral sleeve has its projecting rim abutting against the internal-gear portion of the tub surrounding said central portion 4, while the flange 11 associated with the second sleeve has in a similar way its projecting rim abutting against the geared portion provided on the outside of the tub, so that said flanges are actually facing each other, while being separated from each other by the wall thickness of the tub around said central portion.

20 With such an arrangement, the advantage is obtained that, when screwing the two sleeves into each other, the respective flanges are tightened from opposite directions against the rear wall of the tub and is fact is instrumental in improving the locking-in of the two sleeves and reducing the strain imposed upon the central portion of said rear wall, since it is involved in its entirety so that it provides a maximum extent of resistance, thereby suffering a minimum extent of deformation, whereas only a small part of such central portion is involved by the strain being applied thereupon in traditional set-ups, said smaller part providing therefore a

lower resistance and being as a result subject to a higher degree of deformation.

5 A further improvement is obtained by providing a ring-shaped sealing gasket 12 in the elbow-type curvature between the second sleeve 9 and the respective external flange 11. As it is shown in Figure 1, said sealing gasket is compressed between the two sleeves when they are tightened into each other, thereby preventing the wash liquor to seep through
10 between the two sleeves, and does not give rise to any drawback in disassembling since it can be replaced most easily.

15 In view of enhancing the capability of the perimetral sleeve 8 to expand following the screwing in of the second sleeve 9, so as to be able to get clamped in a still tighter way against the inner cylindrical wall of the through-hole and thereby further improve the solidity and resistance of the coupling between said sleeve and the rear wall, it has been
20 found advantageous to provide said first peripheral sleeve with a plurality of slits 13 running in a parallel arrangement with respect to the axis of the same sleeve and appropriately extending into a portion of the thickness thereof (Figure 6). In such a manner, said sleeve becomes moderately elastic in a
25 radial direction and therefore enables said two sleeves to be more effectively coupled and clamped against said rear wall.

30 A further improvement consists in providing a screwing and locking arrangement of said second sleeve 9, whereby the latter can be screwed into said first sleeve in a particularly convenient manner and, once screwed in, it is automatically locked in position.

35 To this purpose, a saw-toothed profile 14 is arranged on the outer edge of the flange 11 of said second sleeve 9, as shown in Figure 4a, and a corresponding appropriate ring-nut portion 15, which is coaxial with said central hub-carrying

portion, is joined to said rear wall and is sized and oriented in such a way that its free end 16 (see Figure 1), which is in turn provided with a plurality of teeth 17 (see Figure 3), is capable to engage some of the saw-teeth of said profile 14.

5 The practical advantage of such an improvement is quite apparent. In fact, in order to screw in said second sleeve 9 it will be sufficient to use an appropriate alligator wrench, or the like, which engages the corresponding saw-toothed
10 profile 14 and causes it to rotate. Then, once it is duly screwed in, said sleeve will further be immediately locked in position by the resistance opposed by the teeth 17 to the saw-teeth of the profile 14 of the respective flange 11.

15 In order to enable said sleeves to be unlocked and disassembled, on the other hand, it will be sufficient that the portion 15 of said ring-nut be just slightly enlarged with an elastic deformation, so as to enable the respective teeth
20 17 to become released from the saw-toothed profile of the outer edge of the flange 11, then letting it rotate so as to unscrew it from the first sleeve 8.

25 Although the invention has been described on the basis of the example represented by some preferred embodiments thereof, and using a generally known terminology, it cannot be considered as been limited by these, since anyone skilled in the art will appreciate that a number of variations and modifications can be further made involving both construction
30 and shape. The appended claims shall therefore be understood to include such possible modifications as anyone skilled in the art is capable of appreciating, and which do not depart from the scope and the real meaning of the present invention.

CLAIMS

1. Clothes washing machine, particularly of the household type, provided with a washing tub made of plastic material and comprising a cylindrically shaped peripheral envelope, a rear wall (2), a circular front wall, and a passing-through hub (3) arranged at the center of said rear wall and inserted in the central hub-carrying portion (4) of said rear wall, said hub carrying in a per se known manner the bearing (7) provided to support the central shaft (5) of the drum (6), characterized in that said hub consists of a first perimetral sleeve (8), which is capable of being inserted from inside the tub and whose outer cylindrical rim engages the inner rim of said cylindrically shaped central hub-carrying portion (4), a second sleeve (9), which is capable of being inserted from outside the tub into the inner cylindrical cavity of said first sleeve and whose outer rim engages the inner rim of said first perimetral sleeve (8), said second sleeve (9) being adapted to support said bearing (7).

2. Clothes washing machine according to claim 1, characterized in that said first perimetral sleeve is provided with a flange (10) abutting against the inner wall of the tub, whereas said second sleeve (9) is provided with a flange (11) abutting against the outer wall of the tub, a ring-shaped sealing gasket means (12) being arranged in correspondence of

the inner curvature between said second sleeve and its flange (11).

3. Clothes washing machine according to claim 2, characterized in that said second sleeve is adapted to be inserted into said first sleeve by screw engagement between appropriate corresponding threads provided on the outer surface of said first sleeve and the inner surface of said second sleeve.

4. Clothes washing machine according to claim 2 or 3, characterized in that full tightening of said second sleeve into said first sleeve causes said respective flanges (10, 11) to become clamped against the surrounding central hub-carrying portion (4) of said tub.

5. Clothes washing machine according to any of the preceding claims, characterized in that in said first perimetral sleeve there are provided a plurality of slits (13) running in a parallel arrangement with respect to the axis of said first perimetral sleeve and extending substantially over the whole longitudinal dimension thereof.

6. Clothes washing machine according to any of the preceding claims, characterized in that a saw-tooth profile (14) is arranged on the outer edge of the flange (11) of said second sleeve (9), and a corresponding ring-nut portion (15), which is coaxial with said central hub-carrying portion, is joined to said rear wall and has its free end (16) provided with a plurality of teeth (17), said profile (14) and said ring-nut portion (15) being sized and arranged so that the teeth (17) of said free end (16) automatically and elastically engage some of the saw teeth of said profile (14).




FIG. 2




FIG. 1











FIG. 3





INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 94/03941A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 D06F37/00 D06F37/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 D06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched.

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 026 018 (N.V. PHILIPS GLOEILAMPENFABRIEKEN) 1 April 1981 see page 14, line 10 - page 16, line 28; figures 2,4,5A,5B,6	1,2,6
A	DE,U,92 15 811 (ZANUSSI ELETTRODOMESTICI S.P.A.) 18 February 1993 cited in the application & IT91PN00040U see claim 1; figures	1
A	EP,A,0 043 429 (INDUSTRIE ZANUSSI S.P.A.) 13 January 1982 see figures	1
A	CH,A,395 914 (AIRNAF S.A.) 14 January 1966 see figure 1	1,3

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

15 February 1995

Date of mailing of the international search report

22.02.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Courrier, G

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/EP 94/03941

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0026018	01-04-81	FR-A- 2465826	27-03-81
		FR-A- 2465825	27-03-81
		FR-A- 2488921	26-02-82
		FR-A- 2488922	26-02-82
		JP-C- 1491613	07-04-89
		JP-A- 56152691	26-11-81
		JP-B- 63036798	21-07-88
DE-U-9215811	18-02-93	ES-Y- 1022932	16-12-93
		FR-A- 2684114	28-05-93
		GB-A, B 2261881	02-06-93
		US-A- 5329791	19-07-94
EP-A-0043429	13-01-82	AT-T- 11309	15-02-85
		JP-C- 1184427	27-12-83
		JP-A- 57081384	21-05-82
		JP-B- 58015160	24-03-83
		US-A- 4423607	03-01-84
CH-A-395914		NONE	

DERWENT- 1995-240695
ACC-NO:
DERWENT- 200512
WEEK:

COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE: Plastics washing tub for washing machine - comprising cylindrical peripheral envelope of thermoplastic material including rear wall, circular front wall and passing-through hub

INVENTOR: DURAZZANI, P

PATENT- ZANUSSI ELETTRODOMESTICI SPA[ZANU] , ELECTROLUX ZANUSSI ELETTRODOMESTICI
ASSIGNEE: SPA[ELEX] , ELECTROLUX ZANUSSI SPA[ELEX]

PRIORITY-DATA: 1993IT-PN00036 (December 23, 1993)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
CN 1076767 C	December 26, 2001	N/A	000	D06F 037/00
WO 9517543 A1	June 29, 1995	E	014	D06F 037/00
EP 736117 A1	October 9, 1996	E	000	D06F 037/00
CN 1137301 A	December 4, 1996	N/A	000	D06F 037/00
US 5699682 A	December 23, 1997	N/A	008	D06F 037/04
EP 736117 B1	January 21, 1998	E	008	D06F 037/00
DE 69408169 E	February 26, 1998	N/A	000	D06F 037/00
ES 2114298 T3	May 16, 1998	N/A	000	D06F 037/00

DESIGNATED- CN US AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT SE DE ES FR GB IT DE ES
STATES: FR GB IT

CITED-DOCUMENTS: CH 395914; DE 9215811 ; EP 26018 ; EP 43429

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
CN 1076767C	N/A	1994CN-0194435	November 28, 1994
WO 9517543A1	N/A	1994WO-EP03941	November 28, 1994
EP 736117A1	N/A	1994WO-EP03941	November 28, 1994
EP 736117A1	N/A	1995EP-0901450	November 28, 1994

EP 736117A1 Based on	WO 9517543	N/A
CN 1137301A N/A	1994CN-0194435	November 28, 1994
US 5699682A N/A	1994WO-EP03941	November 28, 1994
US 5699682A N/A	1996US-0628742	April 15, 1996
US 5699682A Based on	WO 9517543	N/A
EP 736117B1 N/A	1994WO-EP03941	November 28, 1994
EP 736117B1 N/A	1995EP-0901450	November 28, 1994
EP 736117B1 Based on	WO 9517543	N/A
DE 69408169E N/A	1994DE-0608169	November 28, 1994
DE 69408169E N/A	1994WO-EP03941	November 28, 1994
DE 69408169E N/A	1995EP-0901450	November 28, 1994
DE 69408169E Based on	EP 736117	N/A
DE 69408169E Based on	WO 9517543	N/A
ES 2114298T3 N/A	1995EP-0901450	November 28, 1994
ES 2114298T3 Based on	EP 736117	N/A

INT-CL (IPC): D06F037/00, D06F037/04 , D06F037/22 , D06F037/26

RELATED-ACC-NO: 1995-008147

ABSTRACTED-PUB-NO: EP 736117B

BASIC-ABSTRACT:

Washing tub of domestic washing machine comprises a cylindrical peripheral envelope of thermoplastic material having a rear wall 2, a circular front wall and a passing-through hub 3 including a perimetral sleeve 8 insertable from inside the tub with an outer cylindrical rim engageable with the inner rim of the cylindrical central hub carrying portion 4, a second sleeve 9 insertable from outside the tub with hub 3 arranged at the centre of the rear wall and inserted into the central hub carrying portion 4 of the rear wall and carrying a bearing 7 for supporting the shaft 5 of the drum.

USE - Providing a securely mounted plastic washing tub.

ADVANTAGE - Resists leakage, wear and loosening.

ABSTRACTED-PUB-NO: US 5699682A

EQUIVALENT-ABSTRACTS:

Washing tub of domestic washing machine comprises a cylindrical peripheral envelope of thermoplastic material having a rear wall 2, a circular front wall and a passing-through hub 3 including a perimetral sleeve 8 insertable from inside the tub with an outer cylindrical rim engageable with the inner rim of the cylindrical central hub carrying portion 4, a second sleeve 9 insertable from outside the tub with hub 3 arranged at the centre of the rear wall and inserted into the central hub carrying portion 4 of the rear wall and carrying a bearing 7 for supporting the shaft 5 of the drum.

USE - Providing a securely mounted plastic washing tub.

ADVANTAGE - Resists leakage, wear and loosening.

Washing tub of domestic washing machine comprises a cylindrical peripheral envelope of thermoplastic material having a rear wall 2, a circular front wall and a passing-through hub 3 including a perimetral sleeve 8 insertable from inside the tub with an outer cylindrical rim engageable with the inner rim of the cylindrical central hub carrying portion 4, a second sleeve 9 insertable from outside the tub with hub 3 arranged at the centre of the rear wall and inserted into the central hub carrying portion 4 of the rear wall and carrying a bearing 7 for supporting the shaft 5 of the drum.

USE - Providing a securely mounted plastic washing tub.

ADVANTAGE - Resists leakage, wear and loosening.

WO 9517543A

CHOSEN- Dwg.1-3,6 Dwg.1/6 Dwg.1/6
DRAWING:

TITLE- PLASTICS WASHING TUB WASHING MACHINE COMPRISE CYLINDER PERIPHERAL ENVELOPE
TERMS: THERMOPLASTIC MATERIAL REAR WALL CIRCULAR FRONT WALL PASS THROUGH HUB

DERWENT-CLASS: F07 X27

CPI-CODES: F03-J01;

EPI-CODES: X27-D01A;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1995-110415

Non-CPI Secondary Accession Numbers: N1995-187627

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.